
				Valvole grezze Stelo rettificato, piatto prelaborato, senza scanalature							
Codice	D [mm] Testa	d [mm] Stelo	L [mm] Lung.			Codice	D [mm] Testa	d [mm] Stelo	L [mm] Lung.		
Bimetallo - acciaio , per aspirazione e scarico, fino a 70 KW/l						Bimetallo - nimonic , per scarico, oltre 70 KW/l					
1	30	4.98	124			1B	30	4.98	124		
2	30	5.48	124			2B	30	5.48	124		
3	30	5.98	139			3B	30	5.98	139		
4	30	6.98	139			4B	30	6.98	139		
5	30	7.98	139			5B	30	7.98	139		
6	34	4.98	124			6B	34	4.98	124		
7	34	5.48	124			7B	34	5.48	124		
8	34	5.98	139			8B	34	5.98	139		
9	34	6.98	139			9B	34	6.98	139		
10	34	7.98	139			10B	34	7.98	139		
11	38	5.48	124			11B	38	5.48	124		
12	38	5.98	139			12B	38	5.98	139		
13	38	6.98	139			13B	38	6.98	139		
14	38	7.98	139			14B	38	7.98	139		
15	41	6.98	139			15B	41	6.98	139		
16	41	7.98	139			16B	41	7.98	139		
17	45	6.98	139			17B	45	6.98	139		
18	45	7.98	139			18B	45	7.98	139		
19	50	6.98	139			19B	50	6.98	139		
20	50	7.98	139			20B	50	7.98	139		
21	53	7.98	139			21B					